

Hyperion Series

300W Fresnel / PC

(ver. 2020/06)



SOURCE

- 300W LED ARRAY
- Source life expectancy: > 50.000 h

	Luminous flux		Colour rendering		
	FN	PC	CRI	TLCI	TM-30
6C*	5'863 lm	4'073 lm	>94	92	94
RGBW	5'518 lm	3'740 lm	>85	90	90
TW	6'259 lm	4'381 lm	>94	92	93
WW	6'130 lm	4'258 lm	>97	97	93
CW	6'436 lm	4'472 lm			

*6C: Red Green Blue Amber Cyan Lime

SOFTWARE FUNCTIONS

- ESD: 8 or 16bit extra soft dimming
- 3 selectable dimmer curves
- Adjustable delay in turning on and off
- PWM LED 500Hz-20KHz
- Amber shift (6C)
- ± Green (6C)
- Color boost (6C, RGBW, TW)
- Calibration function (6C, RGBW, TW)
- Service channel
- Stand-alone
- Master Slave
- Hour-counter on single LED
- Storage and factory recovery
- Upgradable Firmware via DMX/USB tool
- Advanced remote settings for all parameters via DMX

CONTROL

- Protocols: DMX512, RDM
- Local potentiometer
- Reversible graphics display with standby-shutdown function
- Wireless ready

	DMX Channels
WHITE	1 / 3 / 6 ch
TW	2 / 5 / 9 ch
RGBW	3 / 6 / 7 / 16 ch
6C	3 / 6 / 7 / 8 / 9 / 21 ch

THERMAL MANAGEMENT

- Wide ventilation slots for better LED cooling with selectable fan speed in: "standard", "silent" and "auto" or DMX regulated
- High efficiency heat pipe cooling system
- No heat load from LED engine towards electronic and vice-versa avoiding the risk of failure due to overheating
- Ta max 40°C

OPTICS

- 200mm High-quality glass lens optics
- Focus: manual

	Beam	
	FN	PC
WHITE	09°-45°	06°-45°
TW	09°-45°	06°-45°
RGBW/6C	12°-45°	08°-45°

PRESETS

- 45-GEL FILTER (6C, RGBW)
- CCT 2700-8000K (6C, RGBW, TW)
- 10 CUSTOM PRESETS (6C, RGBW, TW)

HOUSING

- Highly resistant body in extruded aluminum and techno-polymer body
- Finishing: Black
- IP 20

ELECTRICAL

- Power supply: 100-240 V – 50/60 Hz
- Power consumption: 300 W
- PF>0.94/230VAC PF>0.98/115VAC at full load

CONNECTION

- Power connector: Chassis PowerCON TRUE1 In/Out
- Additional cable: 2m H05RN-F cable with powerCON TRUE1 female cable connector
- DMX: XLR 5-pole In/Out panel connectors

OPTIONS

- Pole Operated Yokes
- ARC Motorized Yokes DMX 512
- Market-standard fixed optics adaptor

COMPLIANCE

- CE
- EN 60598-1; EN 60598-2-17
- SSL Licensing Program
- Manufactured in Italy with Quality System ISO 9001:2015

DIMENSIONS

FN	8.6 Kg	480*425*295 mm
PC	9.8 Kg	570*470*295 mm

Hyperion Series

300W Fresnel / PC

(ver. 2020/06)



DMX chart

	WHITE			TUNABLE WHITE		
	1CH	3CH	6CH	EASY	SPLIT	FULL
	8 BIT	8 BIT	16 BIT	8 BIT	8 BIT	16 BIT
1 ch	DIMMER		DIMMER	DIMMER	DIMMER	DIMMER
2 ch		STROBO	DIMMER FINE	CCT	WW	DIMMER FINE
3 ch		SERVICE	DELAY		CW	CCT
4 ch			FAN		STROBO	WW +/-
5 ch			STROBO		SERVICE	CW +/-
6 ch			SERVICE			DELAY
7 ch						FAN
8 ch						STROBO
9 ch						SERVICE

	RGBW				
	EASY	HSI	CMY	RGBW	FULL
	8 BIT	8 BIT	8 BIT	8 BIT	16 BIT
1 ch	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER
2 ch	CCT	HUE	CYAN	RED	DIMMER FINE
3 ch	COLOUR PRESET	HUE FINE	MAGENTA	GREEN	RED
4 ch		SATURATION	YELLOW	BLUE	RED FINE
5 ch		STROBO	STROBO	WHITE	GREEN
6 ch		SERVICE	SERVICE	STROBO	GREEN FINE
7 ch				SERVICE	BLUE
8 ch					BLUE FINE
9 ch					WHITE
10 ch					WHITE FINE
11 ch					CCT
12 ch					COLOUR PRESET
13 ch					DELAY
14 ch					FAN
15 ch					STROBO
16 ch					SERVICE

	RGBACL						
	EASY	CMY	RGB	HSI	RGBACL	THEATER	FULL
	8 BIT	8 BIT	8 BIT	8 BIT	8 BIT	16 BIT	16 BIT
1 ch	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER	DIMMER
2 ch	CCT	CYAN	RED	HUE	RED	DIMMER FINE	DIMMER FINE
3 ch	COLOUR PRESET	MAGENTA	GREEN	HUE FINE	GREEN	CCT	RED
4 ch		YELLOW	BLUE	SATURATION	BLUE	+/- GREEN	RED FINE
5 ch		STROBO	STROBO	CCT	AMBER	DELAY	GREEN
6 ch		SERVICE	SERVICE	STROBO	CYAN	FAN	GREEN FINE
7 ch				SERVICE	LIME	STROBO	BLUE
8 ch					STROBO	SERVICE	BLUE FINE
9 ch					SERVICE		AMBER
10 ch							AMBER FINE
11 ch							CYAN
12 ch							CYAN FINE
13 ch							LIME
14 ch							LIME FINE
15 ch							COLOUR PRESET
16 ch							CCT
17 ch							+/- GREEN
18 ch							DELAY
19 ch							FAN
20 ch							STROBO
21 ch							SERVICE

Hyperion Series

300W Fresnel / PC

(ver. 2020/06)



4 m	6 m	8 m	10 m	12 m
-----	-----	-----	------	------

Model	Type	CT	CRI	Beam	Lux	Ø Beam	Lux	Ø Beam	Lux	Ø Beam	Lux	Ø Beam	Lux	Ø Beam	(measure at)
FN HY LED 300	WW	3200K	95	9°	14609	0,6	6493	0,9	3652	1,3	2338	1,6	1623	1,9	3200K
				45°	1094	3,3	486	4,9	273	6,6	175	8,2	122	9,9	
	CW	5600K	95	9°	15340	0,6	6818	0,9	3835	1,3	2454	1,6	1704	1,9	5600K
				45°	1148	3,3	510	4,9	287	6,6	184	8,2	128	9,9	
	TW	2700-6500K	95	9°	10497	0,6	4665	0,9	2624	1,3	1680	1,6	1166	1,9	5600K
				45°	834	3,3	371	4,9	209	6,6	134	8,2	93	9,9	
	RGBW	2700-8000K	85	12°	7720	0,8	3431	1,3	1930	1,7	1235	2,1	858	2,5	Full Ch
				45°	984	3,3	438	4,9	246	6,6	158	8,2	109	9,9	
	6C	2700-8000K	97	12°	8359	0,8	3715	1,3	2090	1,7	1337	2,1	929	2,5	Full Ch
				45°	1046	3,3	465	4,9	262	6,6	167	8,2	116	9,9	
PC HY LED 300	WW	3200K	95	6°	17477	0,0	7768	0,6	4369	0,8	2796	1,0	1942	1,2	3200K
				45°	760	3,3	338	4,9	190	6,6	122	8,2	84	9,9	
	CW	5600K	95	6°	18351	0,4	8156	0,6	4588	0,8	2936	1,0	2039	1,2	5600K
				45°	798	3,3	355	4,9	199	6,6	128	8,2	89	9,9	
	TW	2700-6500K	95	6°	12558	0,4	5581	0,6	3139	0,8	2009	1,0	1395	1,2	5600K
				45°	580	3,3	258	4,9	145	6,6	93	8,2	64	9,9	
	RGBW	2700-8000K	85	8°	8938	0,6	3973	0,8	2235	1,1	1430	1,4	993	1,7	Full Ch
				45°	667	3,3	297	4,9	167	6,6	107	8,2	74	9,9	
	6C	2700-8000K	97	8°	10000	0,6	4444	0,8	2500	1,1	1600	1,4	1111	1,7	Full Ch
				45°	727	3,3	323	4,9	182	6,6	116	8,2	81	9,9	