

# CHRISTIE M 4K25 RGB

PRELIMINARY

Live events and projection mapping | Auditoriums and conference centers |  
Planetariums and museums | Theme park attractions | Sports venues | Hospitality and tourism

## An icon, re-imagined

How do you improve on your most iconic projector series?  
Go beyond what everyone believes is possible, that's how.

Introducing the smallest, lightest, quietest, all-in-one RGB pure laser projector on the market. The Christie® M 4K25 RGB re-imagines and reinvents the rugged and reliable M Series industry workhorse with innovative, cutting-edge RGB pure laser technology.

With 25,000 lumens and an incredibly small form factor, the versatile M 4K25 RGB is a new peak of perfection for our 3DLP® RGB pure laser projection technology. The new M 4K25 RGB is ultra-quiet and features double the brightness, double the color volume capability, and quadruple the resolution over our legacy M Series.

With a field-replaceable laser optical system (LOS) and the ability to maintain up to 50,000 hours of continuous light output at 50% brightness, the M 4K25 RGB enables excellent performance in the most demanding and long-life applications.

### Key features

- › UHD 4K resolution with TruLife+™ electronics. All the connections you need are built-in including Christie Terra® SDVoE connectivity for uncompressed 4K content with zero-frame latency.
- › Electronic color convergence (ECC) gives you the ability to select red, green, or blue individually and converge via remote control from the screen or event floor.
- › The intelligent lens system (ILS1) is compatible with legacy M, J, and Crimson Series projector lenses.
- › Our proprietary LiteLOC™ technology automatically manages your brightness over time in higher ambient temperatures and more humid environments to ensure your presentation is the same as day-one.
- › Operates on 220 VAC at full-brightness or 110 VAC at half-brightness, more than doubling the lifetime of the laser optical system (LOS).



**CHRISTIE®**

## Technical specifications

## Christie M 4K25 RGB

Image	brightness	<ul style="list-style-type: none"> <li>• 25,000 ISO lumens</li> <li>• 22,500 ANSI<sup>1,2</sup></li> </ul>
	contrast	<ul style="list-style-type: none"> <li>• 2000:1 On/Off<sup>2</sup></li> <li>• 7000:1 On/Off<sup>3</sup> with optional HC lenses</li> </ul>
Display technology	type	• Dust-sealed 3DLP® (0.95")
	resolution	<ul style="list-style-type: none"> <li>• 3840 x 2160 precision pixel shifted (UHD 4K)</li> <li>• 1920 x 1080 native</li> </ul>
Sound		• 46 dBA <sup>4</sup>
Illumination	type	• Solid state pure RGB (red, green & blue) laser optical system (LOS)
	performance	<ul style="list-style-type: none"> <li>• 25,000 hours<sup>5</sup></li> <li>• Up to 50,000 hours of continuous light output at 50% brightness</li> </ul>
	field replaceable	• Yes
Orientation		• Omnidirectional
Image processing		• Christie TruLife+ electronics, 1.2Gpx/s
Frame rates	standard	• 24-60Hz
	optional	<ul style="list-style-type: none"> <li>• Mirage option: 96-120Hz 4K in 2D or 3D @ 60Hz per eye</li> <li>• Mirage Pro option: Mirage + 240-480Hz HD scaled</li> </ul>
Inputs	standard	<ul style="list-style-type: none"> <li>• 4 x 12G-SDI</li> <li>• 2 x HDMI 2.0</li> <li>• 2 x DisplayPort 1.2</li> <li>• Fiber (QSFP+) for use with optional Christie Link Transmitter (1 input/1 output)</li> <li>• HDBaseT</li> <li>• Terra® (SDVoE)</li> <li>• 3D sync (in/out)</li> <li>• Audio out</li> </ul>
	optional	<ul style="list-style-type: none"> <li>• Christie Twist™ (software can be downloaded at no extra charge)</li> <li>• Christie Twist Premium and Twist Pro</li> </ul>
Automated warping and blending	standard	• Mystique Lite™ (software can be downloaded at no extra charge and requires an off-the-shelf Web/Ethernet camera.)
	optional	• Mystique Essentials • Mystique ProAV • Mystique Large Scale Experience Edition
Multi-projector management	optional	• Christie Conductor software monitors and controls up to 256 projectors and can be downloaded at no extra charge
Lenses (available in standard and UHC)	standard	<ul style="list-style-type: none"> <li>• 0.37:1 ILS1 lens</li> <li>• 0.67:1 ILS1 lens</li> <li>• 0.9:1 ILS1 lens</li> <li>• 0.8-1.16:1 ILS1 lens</li> <li>• 1.1:1 ILS1 lens</li> <li>• 1.16-1.49:1 ILS1 lens</li> </ul>
	high contrast	<ul style="list-style-type: none"> <li>• 1.4-1.8:1 ILS1 lens</li> <li>• 1.8-2.6:1 ILS1 lens</li> <li>• 2.6-4.1:1 ILS1 lens</li> <li>• 4.1-6.9:1 ILS1 lens<sup>6</sup></li> <li>• 6.9-10.4:1 ILS1 lens<sup>6</sup></li> </ul>
Power	line voltage	<ul style="list-style-type: none"> <li>• 200-240 VAC 13A 50/60 Hz Single phase</li> <li>• Limited brightness mode: 100-120 VAC 13A 50/60 Hz at half brightness</li> <li>• Connector: IEC C14 PDU Locking Cord (IEC C13 compatible)</li> </ul>
	Power consumption	• 2600W max (8,870 BTU/hr)
Cooling		• Liquid, self-contained
Laser class		• Class 1 – Risk Group 3
Operating environment		• 5-40°C (41-104°F)
		• Relative humidity: 10-80% non-condensing
Dimensions	size (LxWxH)	• 24.3 x 20.7 x 106.6" - (617 x 525 x 270 mm) <sup>7</sup>
	weight	• 92 lbs. (41.7 kg) <sup>7</sup>

<sup>1</sup> D65 white point measured at 23°C (73.4°F).

<sup>2</sup> Standard fan mode.

<sup>3</sup> Brightness is reduced by 30% with use of high-contrast lens

<sup>4</sup> In standard fan modes up to 22°C for 46 dBA. Up to 48 dBA from 23 - 26°C. From 26 - 40°C gradually increasing up to 55 dBA. 55dBA if the projector is in performance mode.

Sound pressure measurement, measuring conditions, and method of notation all comply with ISO 7779:1999.

<sup>5</sup> To 50% brightness. Based on 9-point average (results may vary depending on environmental conditions i.e., ambient temperature, humidity, dust, smog, or other contaminants.)

<sup>6</sup> New or legacy M, J, and Crimson Series projector lenses require lens hood extension for Class 1 RG3.

<sup>7</sup> Without lens.

Specifications subject to change without notice

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
 CD2242\_Christie M 4K25 RGB\_Preliminary Datasheet\_Sept-21

